

ES G2 Series

3-6kW | Single Phase | 2 MPPTs
Hybrid inverter (LV)

The GoodWe ES G2 inverter is a single-phase hybrid inverter designed to increase self-consumption of generated solar energy, with the ability to control the flow of energy intelligently. The inverter has the functionality of providing backup modes with quick switching time in less than 10ms, that can cover heavy loads such as air conditioning. Its smart design also supports parallel connection for a dependable backup power supply. Installation is also easier and quicker thanks to a compact, lightweight design, with plug and play connection. The ES G2 is compatible with a wide range of low voltage batteries such as the GoodWe Lynx Home U Series battery. The ES G2 is the ideal inverter for homeowners looking to achieve a high degree of energy autonomy, reliable power supply, and lower energy bills.



Smart Control & Monitoring

- Smart load control with dry contacts
- Smart home integration with multi-protocol communications



Superb Safety & Reliability

- Optional AFCI on DC side¹
- Remote Shutdown



Friendly & Thoughtful Design

- Plug & Play
- Elegant and compact design



Flexible & Adaptable Applications

- Maximum 16A DC input current per string and high-power module compatibility
- Strong backup power supply

Technical Data		GW3000-ES-20 GW3600-ES-20 GW3600M-ES-20 GW5000-ES-20 GW5000M-ES-20 GW6000-ES-20 GW6000M-ES-20					
Battery Input Data							
Battery Type ^{1*6}	Li-Ion / Lead-acid	Li-Ion / Lead-acid	Li-Ion	Li-Ion / Lead-acid	Li-Ion	Li-Ion / Lead-acid	Li-Ion
Nominal Battery Voltage (V)				48			
Battery Voltage Range (V)				40 ~ 60			
Max. Continuous Charging Current (A) ¹	60	75	60	120	60	120	60
Max. Continuous Discharging Current (A) ¹	60	75	60	120	60	120	60
Max. Charging Power (W) ^{1*5}	3000	3600	3000	5000	3000	6000	3000
Max. Discharging Power (W) ⁵	3200	3900	3200	5300	3200	6300	3200
PV String Input Data							
Max. Input Power (W) ²	6000	7200	7200	10000	10000	12000	12000
Max. Input Voltage (V) ⁴				600			
MPPT Operating Voltage Range (V) ^{**}				60 ~ 550			
Start-up Voltage (V)				58			
Nominal Input Voltage (V)				360			
Max. Input Current per MPPT (A)				16			
Max. Short Circuit Current per MPPT (A)				23			
Number of MPP Trackers	1	2	2	2	2	2	2
Number of Strings per MPPT				1			
AC Output Data (On-grid)							
Nominal Apparent Power Output to Utility Grid (VA)	3000	3680	3680	5000 ^{**3}	5000 ^{**3}	6000 ^{**3}	6000 ^{**3}
Max. Apparent Power Output to Utility Grid (VA)	3000	3680	3680	5000 ^{**3}	5000 ^{**3}	6000 ^{**3}	6000 ^{**3}
Max. Apparent Power from Utility Grid (VA)	6000	7360	3680	10000	5000	10000	6000
Nominal Output Voltage (V)				220 / 230 / 240			
Output Voltage Range (V)				170 ~ 280			
Nominal AC Grid Frequency (Hz)				50 / 60			
Max. AC Current Output to Utility Grid (A)	13.6	16.7	16.7	22.7	22.7	27.3	27.3
Max. AC Current From Utility Grid (A)	27.3	33.5	16.7	43.5	22.7	43.5	27.3
Nominal Output Current (A)	13.0	16.0	16.0	21.7	21.7	26.1	26.1
Power Factor				~1 (Adjustable from 0.8 leading to 0.8 lagging)			
Max. Total Harmonic Distortion				<3%			
AC Output Data (Back-up)							
Back-up Nominal Apparent Power (VA)	3000	3680	3680	5000	5000	6000	6000
Max. Output Apparent Power (VA)	3000 (6000@10sec)	3680 (7360@10sec)	3680	5000 (10000@10sec)	5000	6000 (10000@10sec)	6000
Max. Output Current (A)	13.6	16.7	16.7	22.7	22.7	27.3	27.3
Nominal Output Voltage (V)				220 / 230 / 240			
Nominal Output Frequency (Hz)				50 / 60			
Output THDv (@Linear Load)				<3%			
Efficiency							
Max. Efficiency				97.6%			
European Efficiency				96.7%			
Max. Battery to AC Efficiency				95.5%			
MPPT Efficiency				99.9%			
Protection							
PV String Current Monitoring				Integrated			
PV Insulation Resistance Detection				Integrated			
Residual Current Monitoring				Integrated			
PV Reverse Polarity Protection				Integrated			
Anti-islanding Protection				Integrated			
AC Overcurrent Protection				Integrated			
AC Short Circuit Protection				Integrated			
AC Overvoltage Protection				Integrated			
DC Switch				Integrated			
DC Surge Protection				Type II			
AC Surge Protection				Type III			
AFCI				Optional			
Remote Shutdown				Integrated			
General Data							
Operating Temperature Range (°C)				-25 ~ +60			
Relative Humidity				0 ~ 95%			
Max. Operating Altitude (m)				3000 (>2000 Derating)			
Cooling Method				Natural Convection			
Display				LED, WLAN + APP			
Communication with BMS				CAN			
Communication with Meter				RS485			
Communication with Portal				WiFi / WiFi + LAN / 4G			
Weight (kg)	19.6	20.8	20.0	21.5	20.0	21.5	20.0
Dimension (W x H x D mm)				505.9 x 434.9 x 154.8			
Topology				Non-isolated			
Self-consumption at Night (W)				<10			
Ingress Protection Rating				IP65			
Mounting Method				Wall Mounted			
Country of Manufacture				China			

*1: The actual charge and discharge current / power also depends on the battery.

*2: The max power is the actual power of PV.

*3: 4600 for DCE-AR-N4105 & NRS 097-2-1.

*4: When the input voltage is greater than 560V, the inverter will enter standby mode. When the voltage returns to below 550V, the inverter will return to normal operation state.

*5: When the PV input voltage is higher than 490V, the battery charging and discharging power will be gradually limited, and the power limitation will be lifted after the input voltage is lowered.

*6: The Li-Ion battery usually contain two mainstream type: LFP and Ternary Lithium battery.

*: Please visit GoodWe website for the latest certificates.

*: All pictures shown are for reference only. Actual appearance may vary.

**: Please refer to the user manual for the MPPT Voltage Range at Nominal Power.