

## BAT-C Series

### 60-112kWh | C&I Battery System

GoodWe's BAT-C Series high-voltage lithium batteries, available in 61.4kWh, 92.1kWh, and 112.6kWh capacities, are specifically designed for small to medium-sized commercial and industrial (C&I) applications. Paired with GoodWe ET 15-30kW and ET 40-50kW hybrid inverters, Static Transfer Switch (STS) box, the BAT-C battery system provides a complete, easy-to-install, and high-performance energy storage solution. This powerful system delivers efficient energy backup, peak shaving, and optimized load management.



#### Flexible & Adaptable Applications

- Max. Continuous 0.9C charging & 1.1C discharging
- Support 4 units in parallel, scaling up to 450kWh
- Pairs with GoodWe ET 15-30kW and ET 40-50kW hybrid inverters



#### Superb Safety & Reliability

- Pack-level humidity monitoring and automatic dehumidification
- Aerosol-based fire suppression system at pack- and cabinet-level



#### Friendly & Thoughtful Design

- Highly integrated cabinet for easy transportation and installation
- Modular design for easier O&M



#### Smart Control & Monitoring

- Remote monitoring & updates
- Cloud-based battery diagnosis and health prediction

Technical Data	GW61.4-BAT-AC-G10	GW92.1-BAT-AC-G10	GW112.6-BAT-AC-G10
<b>Battery System</b>			
Cell Type	LFP (LiFePO4)		
Cell Capacity (Ah)	100		
Rated Capacity (Ah)	200		
Pack Type / model	GW10.2-PACK-ACI-G10		
Pack Nominal Energy (kWh)	10.24		
Pack Configuration	2P96S	2P144S	2P176S
Pack Weight (kg)	<90		
Number of Packs	6	9	11
Nominal Energy (kWh)	61.4	92.1	112.6
Usable Energy (kWh) <sup>1</sup>	60	90	110
Nominal Voltage (V)	307.2	460.8	563.2
Operating Voltage Range (V)	275.52 ~ 346.56	413.28 ~ 519.84	505.12 ~ 635.36
Charging Operating Temperature Range (°C)	-20 ~ +55		
Discharging Operating Temperature Range (°C)	-20 ~ +55		
Max. Charge / Discharge Current (A) <sup>2</sup>	180 / 220		
Max. Charge / Discharge Rate <sup>2</sup>	0.9C / 1.1C		
Max. Charge / Discharge power (kW) <sup>2</sup>	55.2 / 67.5	82.9 / 101.3	101.3 / 123.9
Cycle Life	≥6000 times until 70% SOH under 25 ± 2°C. 0.5C and 98% DOD		
Depth of Discharge	98%		
<b>Efficiency</b>			
Round-trip Efficiency	96%@98%DOD, 0.2C, 25 ± 2°C		
<b>General Data</b>			
Operating Temperature Range (°C)	-20 ~ +55		
Storage Temperature (°C)	+35 ~ +45 (<6 Months); -20 ~ +35 (<1 Year)		
Relative Humidity	0 ~ 100% (Condensationless)		
Max. Operating Altitude (m)	4000		
Cooling Method	Air Conditioner		
User Interface	LED		
Communication	CAN (RS485 Optional)		
Weight (kg)	<950	<1220	<1400
Dimension (W × H × D mm)	1055 × 2000 × 1055		
Noise Emission (dB)	≤70		
Ingress Protection Rating	IP55		
Anti-corrosion Class	C4 (C5-M Optional)		
Fire safety equipment	Aerosol (Pack&Cabinet Level)		
<b>Certification<sup>3</sup></b>			
Safety Regulation	IEC62619 / IEC63056 / IEC60730 / IEC62477 / VDE2510 / ISO13849 IEC62040 / N140 / EU 2023 / 1542 / UN38.3		
EMC	IEC / EN61000-6-1 / 2 / 3 / 4		

\*1: Test conditions, 98% DOD, 0.2C charge & discharge at +25 ± 2°C for battery system at beginning life. System Usable Energy may vary with system configuration.

\*2: Actual Dis-/Charge Current and power derating will occur related to Cell Temperature and SOC. And, Max C-rate continuous time is affected by SOC, Cell Temperature, Atmosphere environment temperature.

\*3: Not all certifications & standards listed, check the official website for detail.

\*: Please visit GoodWe website for the latest certificates.