GOODWE

4G Module

The GoodWe 4G Module is easy to install with Plug & Play design and can support several operators worldwide, offering customers convenience and reliability, especially in remote areas without access to Wi-Fi.





IP65



Plug & Play*1



Stable and reliable



Wide range of applications

Model	4G Kit-EC	4G Kit-AU
General Data		
Max. Inverters Supported	1	
Connection Interface	USB	
nstallation	Plug and Play ^{*1}	
ndicator	LED Indicator	
Dimensions (W \times H \times D mm)	49 × 96 × 32	
Standard SIM Card Size (mm)	25 × 15	
ngress Protection Rating	IP65	
Power Consumption (W)	<4	
Operating Temperature Range (°C)	-30 ~ +60	
Storage Temperature Range (°C)	-40 ~ +70	
Relative Humidity	0-100% (non-condensing)	
Max. Operating Altitude (m)	4000	
Vireless Parameter		
TE-FDD	B1 / B3 / B7 / B8 / B20 / B28A	
TE-TDD	-	B40
VCDMA	B1 / B8	B1 / B2 / B5 / B8
GSM / GPRS	B3 / B8	

^{*:} Please visit GoodWe website for the latest certificates.

^{*1:} APN parameters must be configured correctly before module operation.